

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A heat seal laminate comprising:
 - a facestock having an upper surface and a lower surface;
 - a heat-activatable layer adhered to said lower surface of said facestock;
 - a laminating adhesive overlying said upper surface of said facestock;
 - a carrier layer adhered to said laminating adhesive; and
 - the heat-activatable layer having an upper surface and a lower surface, the upper surface of the heat activatable layer being adhered to said lower surface of said facestock, a layer of ink or graphics overlying the lower surface of the heat-activatable layer;

 said heat-activatable layer comprising a heat-activatable adhesive or thermoplastic film selected from the group consisting of polyolefins, polyamides, polyester copolymers, polyurethanes, ionomers based on sodium or zinc salts of ethylene methacrylic acid, polyacrylonitriles, ethylene-vinyl acetate copolymers, ethylene methacrylic acid, ethylene methyl acrylate, ethylene acrylic acid, ethylene ethyl acrylate, and mixtures of two or more thereof.
2. (Original) The heat seal laminate of claim 1 wherein said facestock comprises a single layer construction.
3. (Original) The heat seal laminate of claim 1 wherein said facestock comprises a multi-layered construction.

4. (Original) The heat seal laminate of claim 1 wherein said heat-activatable layer comprises a polyurethane based adhesive.
5. (Original) The heat seal laminate of claim 1 wherein said facestock comprises a polyvinyl chloride film.
6. (Currently Amended) The heat seal laminate of claim 1 wherein said laminating adhesive comprises ~~a radiation-cured adhesive material or a removable pressure-sensitive adhesive material~~.
7. (Original) The heat seal laminate of claim 1 wherein said laminating adhesive comprises a radiation-cured adhesive material.
8. (Original) The heat seal laminate of claim 1 further comprising a detack layer having an upper surface and a lower surface, the upper surface of said detack layer adhered to the lower surface of the heat-activatable layer, the layer of ink or graphics being printed on the lower surface of the detack layer.